

Patent  
2024677-7033292001

**AMENDMENTS TO THE CLAIMS**

Please cancel claims 42 and 43 without prejudice to pursue these claims in a related application. A complete listing of the claims is provided below.

1. (Previously Presented) A system for receiving a communication signal, the system comprising:
  - an antenna that can be coupled to a subscriber terminal;
  - a compass secured to the antenna, the compass being adapted to measure an orientation of the antenna;
  - a memory unit for storing data associated with a desired mounting configuration of the antenna, wherein the data comprises information regarding a position of a stationary base station; and
  - a processor coupled to the compass and the memory unit, the processor configured to generate a signal based on a measured orientation of the antenna by the compass and data stored in the memory unit.
2. (Original) The system of claim 1, wherein the data is associated with a desired azimuth angle of the antenna.
3. (Original) The system of claim 2, wherein the processor is configured to generate the signal when a measured azimuth angle of the antenna is substantially the same as, or within a prescribed threshold from, the desired azimuth angle of the antenna.
4. (Original) The system of claim 2, wherein the processor is configured to generate the signal when a measured azimuth angle of the antenna is not substantially the same as, or beyond a prescribed threshold from, the desired azimuth angle of the antenna.
5. (Original) The system of claim 1, further comprising an indicator configured to receive the signal from the processor.

Patent  
2024677-7033292001

6. (Original) The system of claim 5, wherein the indicator comprises a light source for generating an optical signal in response to the signal generated by the processor.
7. (Original) The system of claim 5, wherein the indicator comprises an audio source for generating an audio signal in response to the signal generated by the processor.
8. (Original) The system of claim 5, wherein the indicator is configured to emit a signal when an orientation of the antenna is substantially the same as, or within a prescribed threshold from, a desired orientation of the antenna.
9. (Original) The system of claim 5, wherein the indicator is configured to emit a signal when an orientation of the antenna is not substantially the same as, or beyond a prescribed threshold from, a desired orientation of the antenna.
10. (Original) The system of claim 1, further comprising:  
a tilt sensor secured to the antenna, the tilt sensor adapted to measure an elevation angle of the antenna;  
wherein the processor is coupled to the tilt sensor, and the processor is further configured to generate a signal based on a measured elevation angle of the antenna and data stored in the memory unit.
11. (Original) The system of claim 10, wherein the stored data comprises data associated with a desired elevation angle of the antenna.
12. (Original) The system of claim 1, further comprising:  
a positional sensor secured to the antenna, the positional sensor adapted to measure a position of the antenna;  
wherein the processor is coupled to the positional sensor, and the processor is further configured to generate a signal based on a measured position of the antenna and data stored in the memory unit.

Patent  
2024677-7033292001

13. (Original) The system of claim 12, wherein the data stored in the memory unit comprises data associated with a desired position of the antenna.
14. (Original) The system of claim 1, further comprising:  
a digital signal processor for processing radio frequency signal received by the antenna;  
wherein the processor is coupled to the digital signal processor and is configured to generate a signal based on a processed radio frequency signal.
15. (Original) The system of claim 14, wherein the processor is configured to generate the signal when the processed radio frequency signal has a desirable quality.
16. (Previously Presented) A device for installing an antenna, comprising:  
a structure attachable to the antenna;  
a compass secured to the structure, the compass being adapted to measure an orientation of the antenna;  
a memory unit for storing data associated with a desired mounting configuration of the antenna, wherein the data comprises information regarding a position of a stationary base station;  
and  
a processor coupled to the compass and the memory unit, the processor configured to generate a signal based on a measured orientation of the antenna by the compass and data stored in the memory unit.
17. (Original) The device of claim 16, wherein the data is associated with a desired azimuth angle of the antenna.
18. (Original) The device of claim 17, wherein the processor is configured to generate the signal when a measured azimuth angle of the antenna is substantially the same as, or within a prescribed threshold from, the desired azimuth angle of the antenna.

Patent  
2024677-7033292001

19. (Original) The device of claim 17, wherein the processor is configured to generate the signal when a measured azimuth angle of the antenna is not substantially the same as, or beyond a prescribed threshold from, the desired azimuth angle of the antenna.
20. (Original) The device of claim 16, further comprising an indicator configured to receive the signal from processor.
21. (Original) The device of claim 20, wherein the indicator comprises a light source for generating an optical signal in response to the signal generated by the processor.
22. (Original) The device of claim 20, wherein the indicator comprises an audio source for generating an audio signal in response to the signal generated by the processor.
23. (Original) The device of claim 20, wherein the indicator is configured to emit a signal when an orientation of the antenna is substantially the same as, or within a prescribed threshold from, a desired orientation of the antenna.
24. (Original) The device of claim 20, wherein the indicator is configured to emit a signal when an orientation of the antenna is not substantially the same as, or beyond a prescribed threshold from, a desired orientation of the antenna.
25. (Original) The device of claim 16, further comprising:  
a tilt sensor secured to the antenna, the tilt sensor adapted to measure an elevation angle of the antenna;  
wherein the processor is coupled to the tilt sensor, and the processor is further configured to generate a signal based on a measured elevation angle of the antenna and data stored in the memory unit.
26. (Original) The device of claim 25, wherein the memory unit comprises data associated with a desired elevation angle of the antenna.

Patent  
2024677-7033292001

27. (Original) The device of claim 17, further comprising:  
a positional sensor secured to the antenna, the positional sensor adapted to measure a position of the antenna;  
wherein the processor is coupled to the positional sensor, and the processor is further configured to generate a signal based on a measured position of the antenna and a stored data in the memory unit.
28. (Original) The device of claim 27, wherein the memory unit comprises data associated with a desired position of the antenna.
29. (Original) The device of claim 16, further comprising:  
a digital signal processor for processing radio frequency signal received by the antenna;  
wherein the processor is coupled to the digital signal processor and is configured to generate a signal based on a processed radio frequency signal.
30. (Original) The device of claim 29, wherein the processor is configured to generate the signal when the processed radio frequency signal has a desirable quality.
31. (Previously Presented) A device for processing data associated with an installation of an antenna, the device comprising a processor, wherein the processor is configured to:  
receive an input associated with a measured orientation of an antenna;  
compare the input with data associated with a desired mounting configuration of the antenna, wherein the data is obtained using a positional data of a stationary base station; and  
generate a signal based on the comparing.
32. (Original) The device of claim 31, wherein the processor is further configured to read the data from a memory unit.

Patent  
2024677-7033292001

33. (Original) The device of claim 31, wherein the processor is configured to receive the input from a circuit based compass.
34. (Original) The device of claim 33, wherein the measured orientation of the antenna comprises an azimuth angle of the antenna, and the desired mounting configuration of the antenna comprises a desired azimuth angle of the antenna.
35. (Original) The device of claim 34, wherein the processor is configured to generate the signal when a measured azimuth angle of the antenna is substantially the same as, or within a prescribed threshold from, the desired azimuth angle of the antenna.
36. (Original) The device of claim 34, wherein the processor is configured to generate the signal when a measured azimuth angle of the antenna is not substantially the same as, or beyond a prescribed threshold from, the desired azimuth angle of the antenna.
37. (Original) The device of claim 31, wherein the processor is configured to receive an input from a tilt sensor.
38. (Original) The device of claim 37, wherein the measured orientation of the antenna comprises an elevation angle of the antenna, and the desired mounting configuration of the antenna comprises a desired elevation angle of the antenna.
39. (Original) The device of claim 38, wherein the processor is configured to generate the signal when a measured elevation angle of the antenna is substantially the same as, or within a prescribed threshold from, the desired elevation angle of the antenna.
40. (Original) The device of claim 38, wherein the processor is configured to generate the signal when a measured elevation angle of the antenna is not substantially the same as, or beyond a prescribed threshold from, the desired elevation angle of the antenna.

Patent  
2024677-7033292001

41. (Original) The device of claim 31, wherein the processor is configured to receive an input from a digital signal processor, and generate the signal when an input from the digital signal processor indicates that a radio frequency signal received by the antenna has a desirable quality.

42-43. (Canceled)

44. (Previously Presented) A method of installing an antenna, comprising:  
securing the antenna to a structure, the antenna carrying a feedback device that provides a signal based on an orientation of the antenna and a desired mounting configuration of the antenna;

adjusting a position or orientation of the antenna based on the signal or an absence of the signal, wherein the step of adjusting is also based on information regarding a position of a stationary base station.

45. (Original) The method of claim 44, wherein the orientation of the antenna comprises an azimuth angle of the antenna, and the desired mounting configuration comprises a desired azimuth angle of the antenna.

46. (Original) The method of claim 44, wherein the orientation of the antenna comprises an elevation angle of the antenna, and the desired mounting configuration comprises a desired elevation angle of the antenna.

47. (Original) The method of claim 44, wherein the signal comprises an optical signal and the adjusting comprises positioning or orienting the antenna based on the optical signal.

48. (Original) The method of claim 44, wherein the signal comprises a termination of an optical signal, and the adjusting comprises positioning or orienting the antenna until the optical signal is terminated.

Patent  
2024677-7033292001

49. (Original) The method of claim 44, wherein the signal comprises an audio signal and the adjusting comprises positioning or orienting the antenna based on the audio signal.
50. (Original) The method of claim 44, wherein the signal comprises a termination of an audio signal, and the adjusting comprises positioning or orienting the antenna until the audio signal is terminated.
51. (Original) The method of claim 44, wherein the signal comprises a text message and the adjusting comprises positioning or orienting the antenna based on the text message.
52. (Original) The method of claim 44, wherein the adjusting comprises changing an elevation angle of the antenna.
53. (Original) The method of claim 44, wherein the adjusting comprises changing an azimuth angle of the antenna.
54. (Original) The method of claim 44, wherein the antenna further carrying a memory unit, and the method further comprising inputting data associated with the desired mounting configuration of the antenna to the memory unit.
55. (Previously Presented) A method of initializing a feedback device secured to an antenna, the feedback device having a memory unit, the method comprising:  
determining data associated with a desired mounting configuration of the antenna; and  
inputting the data to the memory unit;  
wherein the data is determined based on a positional information of a base station.
56. (Original) The method of claim 55, wherein the data comprises a desired orientation of the antenna.



Patent  
2024677-7033292001

57. (Original) The method of claim 56, wherein the desired orientation comprises a desired azimuth angle of the antenna.

58. (Original) The method of claim 56, wherein the desired orientation comprises an elevation angle of the antenna.

59. (Original) The method of claim 56, further comprising determining the desired orientation of the antenna.

60. (Original) The method of claim 59, wherein the determining the desired orientation of the antenna comprises:

determining a position of a base station from which signal is to be received by the antenna;

determining a position of the structure to which the antenna is to be secured; and

determining a desired azimuth angle of the antenna based on the positions of the base station and the structure.

61. (Original) The method of claim 59, wherein the determining the desired orientation of the antenna comprises:

determining a distance between a base station from which signal is to be received by the antenna and a position of the structure to which the antenna is to be secured;

determining a relative vertical distance between the antenna and the base station;

determining a desired elevation angle of the antenna based on the distance and the relative vertical distance.

62. (Canceled)